

**AMENDMENTS TO THE CLAIMS**

1. (Currently Amended) A device comprising a NO<sub>x</sub> removal system for removing nitrogen oxides from a nitrogen oxide containing combustion exhaust, said NO<sub>x</sub> removal system comprising a NO<sub>x</sub> treatment section, a diverter, and a hydrogen generation section, wherein:  
    said NO<sub>x</sub> treatment section is configured to remove nitrogen oxides from said exhaust;  
    said diverter is configured to enable delivery of water to said hydrogen generation section, and is further configured to extract water from said combustion exhaust;  
    said hydrogen generation section is configured to deliver hydrogen to said NO<sub>x</sub> treatment section; and  
    said NO<sub>x</sub> removal system is configured such that said delivery of said hydrogen to said NO<sub>x</sub> treatment section is substantially isolated from delivery of a substantial amount of oxygen to said NO<sub>x</sub> treatment section.
2. (Original) A device as claimed in claim 1 wherein said exhaust comprises oxygen.
3. (Original) A device as claimed in claim 1 wherein said NO<sub>x</sub> removal system is configured such that said delivery of said hydrogen to said NO<sub>x</sub> treatment section is substantially isolated from delivery of said exhaust to said NO<sub>x</sub> treatment section.
4. (Original) A device as claimed in claim 1 wherein said NO<sub>x</sub> treatment section is configured to remove nitrogen oxides from said exhaust through adsorption.
5. (Original) A device as claimed in claim 4 wherein said NO<sub>x</sub> treatment section comprises a plurality of catalyst beds.
6. (Original) A device as claimed in claim 1 wherein said NO<sub>x</sub> treatment section comprises at least one NO<sub>x</sub> adsorber.
7. (Original) A device as claimed in claim 1 wherein said NO<sub>x</sub> treatment section defines at least two independent NO<sub>x</sub> treatment zones.

8. (Original) A device as claimed in claim 7 wherein said independent NO<sub>x</sub> treatment zones are defined by independent NO<sub>x</sub> adsorbers.

9. (Original) A device as claimed in claim 7 wherein said independent NO<sub>x</sub> treatment zones are defined by multiple catalyst beds packaged as a single NO<sub>x</sub> adsorber unit.

10. (Original) A device as claimed in claim 7 wherein said NO<sub>x</sub> removal system is configured to deliver said exhaust to one of said independent NO<sub>x</sub> treatment zones on a selective basis.

11. (Original) A device as claimed in claim 10 wherein said delivery of said exhaust is affected by a flow diverter valve.

12. (Original) A device as claimed in claim 10 wherein said NO<sub>x</sub> removal system is configured to deliver said hydrogen from said hydrogen generation section to one of said independent NO<sub>x</sub> treatment zones on a selective basis.

13. (Original) A device as claimed in claim 12 wherein said NO<sub>x</sub> removal system is configured to deliver said hydrogen and said exhaust to said NO<sub>x</sub> treatment section such that each is delivered to different ones of said independent NO<sub>x</sub> treatment zones on a selective basis.

14. (Original) A device as claimed in claim 1 wherein said diverter is positioned downstream of said NO<sub>x</sub> treatment section.

15. (Canceled)

16. (Original) A device as claimed in claim 1 wherein said diverter comprises a condensation unit or a semi-permeable membrane.

17. (Original) A device as claimed in claim 1 wherein said hydrogen generation section is configured to deliver an amount of hydrogen sufficient to affect desulfation of said NO<sub>x</sub> treatment section.

18. (Original) A device as claimed in claim 1 wherein said hydrogen generation section is configured to deliver an amount of hydrogen sufficient to affect catalytic regeneration of said NO<sub>x</sub> treatment section.

19. (Original) A device as claimed in claim 1 wherein said hydrogen generation section is configured to accumulate and store hydrogen.

20. (Original) A device as claimed in claim 19 wherein said hydrogen generation section further comprises a pressure monitor configured to monitor said accumulation and storage of hydrogen.

21. (Original) A device as claimed in claim 1 wherein said hydrogen generation section comprises an electrolysis unit.

22. (Original) A device as claimed in claim 1 wherein said hydrogen generation section comprises a hydrogen storage reservoir fed by a hydrogen output of said electrolysis unit.

23. (Original) A device as claimed in claim 1 wherein said hydrogen generation section is configured to deliver hydrogen to one of at least two independent NO<sub>x</sub> treatment zones of said NO<sub>x</sub> treatment section on a selective basis.

24. (Original) A device as claimed in claim 1 wherein said hydrogen generation section comprises at least one hydrogen injector.

25. (Original) A device as claimed in claim 1 wherein:

said hydrogen generation section comprises a pair of hydrogen injectors; and  
each of said hydrogen injectors is in communication with different independent NO<sub>x</sub> treatment zones of said NO<sub>x</sub> treatment section.

26. (Original) A device as claimed in claim 1 wherein:

said device comprises an engine configured to generate torque; and

said engine generates said exhaust.

27. (Original) A device as claimed in claim 26 wherein said engine comprises a diesel engine.

28. (Original) A device as claimed in claim 26 wherein said engine is configured such that said exhaust is characterized by an oxygen content of about 1 to about 20 percent, by weight.

29. (Original) A device as claimed in claim 26 wherein:

said device comprises an electrical generator driven by said engine; and

said hydrogen generation section is powered by said electrical generator.

30. (Original) A device as claimed in claim 26 wherein said device comprises at least one exhaust treatment system in addition to said NO<sub>x</sub> treatment section.

31. (Original) A device as claimed in claim 1 wherein said NO<sub>x</sub> removal system comprises a controller programmed to control delivery of said exhaust to said NO<sub>x</sub> treatment section.

32. (Original) A device as claimed in claim 31 wherein said controller is programmed to:

monitor a condition indicative of removal of said nitrogen oxides by at least one treatment zone of said NO<sub>x</sub> treatment section; and

divert exhaust from said treatment zone when said treatment zone approaches its nitrogen oxide removal capacity.

33. (Original) A device as claimed in claim 32 wherein said controller is programmed to affect delivery of said hydrogen to said treatment zone following diversion of said exhaust from said treatment zone.

34. (Original) A device as claimed in claim 1 wherein said NO<sub>x</sub> removal system further comprises a controller programmed to control delivery of said hydrogen to said NO<sub>x</sub> treatment section.

35. (Original) A device as claimed in claim 34 wherein:

said NO<sub>x</sub> treatment section defines at least two independent NO<sub>x</sub> treatment zones; and  
said controller is programmed to deliver said exhaust and said hydrogen respectively to different ones of said independent NO<sub>x</sub> treatment zones.

36. (Original) A device as claimed in claim 34 wherein said controller is configured to monitor accumulation and storage of hydrogen in said hydrogen generation section.

37. (Original) A device as claimed in claim 36 wherein monitoring of said accumulation and storage of hydrogen is affected through a pressure monitor in communication with said controller.

38. (Original) A device as claimed in claim 1 wherein said device comprises:

a vehicle body or stationary device;  
an engine configured to generate said exhaust and sufficient torque to accelerate said vehicle body or power said stationary device.

39-47 (Canceled)

48. (Currently Amended) A device comprising a combustion engine and a NO<sub>x</sub> removal system for removing nitrogen oxides from ~~an~~ a combustion exhaust generated by said engine, said NO<sub>x</sub> removal system comprising a NO<sub>x</sub> treatment section, a diverter, and a hydrogen generation section, wherein:

said exhaust comprises oxygen and nitrogen oxides;  
said NO<sub>x</sub> treatment section is configured to remove nitrogen oxides from said exhaust;  
said diverter is configured to enable delivery of water to said hydrogen generation section, and is further configured to extract water from the combustion exhaust;  
said hydrogen generation section is configured to deliver hydrogen to said NO<sub>x</sub> treatment section; and  
said NO<sub>x</sub> removal system is configured such that said delivery of said hydrogen to said NO<sub>x</sub> treatment section is substantially isolated from delivery of a substantial amount of said

oxygen in said exhaust to said NO<sub>x</sub> treatment section.

49. (New) A device comprising a NO<sub>x</sub> removal system for removing nitrogen oxides from a nitrogen oxide containing exhaust, said NO<sub>x</sub> removal system comprising a NO<sub>x</sub> treatment section, a diverter, and a hydrogen generation section, wherein:

said NO<sub>x</sub> treatment section is configured to remove nitrogen oxides from said exhaust, wherein said NO<sub>x</sub> treatment section defines at least two independent NO<sub>x</sub> treatment zones;

said diverter is configured to enable delivery of water to said hydrogen generation section;

said hydrogen generation section is configured to deliver hydrogen to said NO<sub>x</sub> treatment section; and

said NO<sub>x</sub> removal system is configured such that said delivery of said hydrogen to said NO<sub>x</sub> treatment section is substantially isolated from delivery of a substantial amount of oxygen to said NO<sub>x</sub> treatment section, and wherein said NO<sub>x</sub> removal system is configured to deliver said exhaust to one of said independent NO<sub>x</sub> treatment zones on a selective basis.